



MODEL 463C (SHOWN)



MODEL 468A (SHOWN)

WOOD SPECIES: BEECH IN 13 FINISHES
SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED
WITH FLEX-WEB FOR ADDED COMFORT
AND SUPPORT.

OPTIONAL FRONT LEG CASTERS AVAILABLE.
ADD \$37 LIST FOR SET OF 2 CASTERS. NOT
AVAILABLE ON BARSTOOLS.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING										
				WOOD	B/COM	C	D/COL	E	F	G	L	M		
ARMLESS MODELS														
463A	ALL WOOD			\$204										
463C	UPHOLSTERED SEAT	.75	9	\$243	\$252	\$266	\$285	\$306	\$328	\$356	\$384			
DIMENSIONS: W 17.375 D 20 H 33 SW 15.75 SD 16.5 SH 18 CARTONED WEIGHT 20 CUBIC FEET 9														
BARSTOOL MODELS														
468A	ALL WOOD			\$237										
468C	UPHOLSTERED SEAT	.75	9	\$276	\$285	\$300	\$318	\$339	\$361	\$390	\$418			
DIMENSIONS: W 19 D 20 H 44.5 SW 17 SD 16.25 SH 30 CARTONED WEIGHT 30 CUBIC FEET 13														

ACCOLADE



MODEL 473C (SHOWN)




MODEL 478A (SHOWN)



WOOD SPECIES: BEECH IN 13 FINISHES
SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED
WITH FLEX-WEB FOR ADDED COMFORT
AND SUPPORT.

OPTIONAL FRONT LEG CASTERS AVAILABLE.
ADD \$37 LIST FOR SET OF 2 CASTERS. NOT
AVAILABLE ON BARSTOOLS.

MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD	B/COM	C	D/COL	E	F	G	L	M
ARM MODELS												
473A	ALL WOOD			\$204								
473C	UPHOLSTERED SEAT	.75	9		\$243	\$252	\$266	\$285	\$306	\$328	\$356	\$384
DIMENSIONS: W 18 D 20 H 35 SW 17 SD 16.5 SH 18 CARTONED WEIGHT 20 CUBIC FEET 9												
												
BARSTOOL MODELS												
478A	ALL WOOD			\$237								
478C	UPHOLSTERED SEAT	.75	9		\$276	\$285	\$300	\$318	\$339	\$361	\$390	\$418
DIMENSIONS: W 19 D 20 H 44.5 SW 17 SD 16.5 SH 30 CARTONED WEIGHT 30 CUBIC FEET 13												



MODEL 483A (SHOWN)



MODEL 488C (SHOWN)

WOOD SPECIES: BEECH IN 13 FINISHES
SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED
WITH FLEX-WEB FOR ADDED COMFORT
AND SUPPORT.

OPTIONAL FRONT LEG CASTERS AVAILABLE.
ADD \$37 LIST FOR SET OF 2 CASTERS. NOT
AVAILABLE ON BARSTOOLS.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING								
				WOOD	B/COM	C	D/COL	E	F	G	L	M
ARM MODELS												
483A	ALL WOOD			\$204								
483C	UPHOLSTERED SEAT	.75	9		\$243	\$252	\$266	\$285	\$306	\$328	\$356	\$384
DIMENSIONS: W 18 D 20 H 35 SW 17 SD 16.5 SH 18				CARTONED WEIGHT 20 CUBIC FEET 9								
BARSTOOL MODELS												
488A	ALL WOOD			\$237								
488C	UPHOLSTERED SEAT	.75	9		\$276	\$285	\$300	\$318	\$339	\$361	\$390	\$418
DIMENSIONS: W 19 D 20 H 44.5 SW 17 SD 16.5 SH 30				CARTONED WEIGHT 30 CUBIC FEET 13								

**SPECIFICATIONS FOR COMMUNITY
ACCOLADE COLLECTION
MODELS: 463A & C – 468A & C**

Wood Species: Beech

Details of Material: Seat: Glued Lumber; 1” thick
Back Posts: Steam Bent Solid Lumber; 1 ¼” thick
Front Posts: Solid Lumber; 1 ½” thick tapering to 1”
Slats: Steam Bent Solid Lumber; ¾” thick
Front Rail: Solid Lumber; ¾” thick
Seat Rim: Solid Lumber; 7/8” thick
Stretcher Rim: Solid Lumber; 11/16” thick
Front Stretcher: Solid Lumber; ¾” thick
Front Corner Blocks: Solid Lumber; 1” thick
Foot Rail: Solid Lumber; ¾” thick

Details of Construction: Top to Back Post Joints: Mortise Tennon and Glue
Horizontal Slat Joints: Mortise Tennon and Glue
Seat Rim to Front Post Joints: Mortise Tennon and Glue
Seat Rim to Back Post Joints: Bolts, Taps and another screw
Stretcher Rim to Front Post Joints: Mortise Tennon, Glue and Screws
Stretcher Rim to Back Post Joints: Screws
Front Assembly Joints: Mortise Tennon and Glue
Corner Blocks: Glue and Screws

Hardware: Each chair is equipped standard with rubber cushion nickel plated glides.

Finish: Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

Adhesive: The assembly glue is a modified synthetic resin emulsion. This premium grade product has a high content of solids (52%) with a quick set time and is well suited for cold press operations.

Upholstery: Each seat is upholstered with 1 ½” thick polyurethane foam in a pneumatic press to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, Technical Bulletin #117.

Dimensions:	<u>463A, C</u>	<u>468A, C</u>
Width:	17 ⅛ ”	Width: 19”
Depth:	20”	Depth: 20”
Height:	33”	Height: 44 ½”
Seat Width:	15 ¾”	Seat Width: 17”
Seat Depth:	16 ½”	Seat Depth: 16 ¼”
Seat Height:	18”	Seat Height: 30”