

ALPINE



CHAIRS STACK UP TO FIVE HIGH



MODEL 393C (SHOWN)



MODEL 398A (SHOWN)



WOOD SPECIES: BEECH IN 13 FINISHES. SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED WITH FLEX-WEB FOR ADDED COMFORT AND SUPPORT.

OPTIONAL LASER ENGRAVED BACK IMPRINT AVAILABLE. SEE PAGE 15 FOR PRICING AND ARTWORK SPECIFICATIONS.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD	B/COM	C	D/COL	E	F	G	L	M
ARMLESS MODELS												
393A	ALL WOOD			\$254								
393C	UPHOLSTERED SEAT	.75	9		\$292	\$302	\$316	\$334	\$355	\$377	\$406	\$434
DIMENSIONS: W 16.5 D 18 H 33 SW 16 SD 15.5 SH 18 CARTONED WEIGHT 21 CUBIC FEET 9												
BARSTOOL MODELS (DOES NOT STACK)												
398A	ALL WOOD			\$302								
398C	UPHOLSTERED SEAT	.75	9		\$340	\$350	\$364	\$383	\$403	\$426	\$454	\$482
DIMENSIONS: W 16.5 D 18 H 44.25 SW 16 SD 15.5 SH 30 CARTONED WEIGHT 28 CUBIC FEET 13												



**SPECIFICATIONS FOR COMMUNITY  
ALPINE COLLECTION  
MODELS: 393A – 393C – 398A – 398C**

**Wood Species:** Beech

**Details of Material:** Seat: Solid wood seat; 1” thick  
Back Posts: Steam bent solid lumber; 1 ¼” thick  
Front Post: Solid lumber; 1 ½” thick  
Top: Bent plywood; ¼” thick  
Seat Rim: Bent plywood; ⅝” thick  
Stretcher Rim: Bent plywood; ¾” thick  
Front Corner-Block: Solid lumber; 1 ⅜”

**Details of Construction:** Top to Back Post Joint: Mortise Tennon and Glue  
Vertical Slat Joint: Mortise Tennon and Glue  
Under Seat Rail Joints: Mortise Tennon and Glue  
Stretcher Joints: Mortise Tennon, Glue and Screws  
Corner Blocks: Glue and Screws

**Hardware:** Each chair is equipped standard with rubber cushion nickel plated glides.

**Finish:** Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

**Adhesives:** The assembly glue is a modified synthetic resin emulsion. This premium grade product has a high content of solids (52%) with a quick set time and is well suited for cold press operations.

**Upholstery:** Each seat is upholstered with 2” high density polyurethane in a pneumatic press to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, and Technical Bulletin #117.

<b>Dimensions:</b>	<b><u>393A &amp; 393C</u></b>	<b><u>398A &amp; 398C</u></b>
	Width: 16 ½”	Width: 16 ½”
	Depth: 18”	Depth: 18”
	Height: 33”	Height: 44 ¼”
	Seat Width: 16”	Seat Width: 16”
	Seat Depth: 15 ½”	Seat Depth: 15 ½”
	Seat Height: 18”	Seat Height: 30”