

## CARRIAGE



MODEL 401C (SHOWN)



MODEL 403A (SHOWN)



MODEL 408A (SHOWN)



WOOD SPECIES: OAK IN 14 FINISHES.  
SEE PAGE 221.

CARRIAGE STOOL HAS A 360° SWIVEL  
CAPABILITY.

MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD	B/COM	C	D/COL	E	F	G	L	M
ARM MODELS												
401A	ALL WOOD			\$365								
401C	UPHOLSTERED SEAT	.75	9		\$415	\$425	\$439	\$458	\$478	\$501	\$529	\$557
DIMENSIONS: W 23 D 23 H 38 SW 19 SD 16 SH 18 AH 28 CARTONED WEIGHT 28 CUBIC FEET 14												
ARMLESS MODELS												
403A	ALL WOOD			\$296								
403C	UPHOLSTERED SEAT	.75	9		\$346	\$355	\$369	\$388	\$409	\$431	\$459	\$487
DIMENSIONS: W 20.5 D 21.5 H 38 SW 18 SD 16 SH 18 CARTONED WEIGHT 21 CUBIC FEET 9												
SWIVEL BARSTOOL MODELS												
408A	ALL WOOD			\$418								
408C	UPHOLSTERED SEAT	.75	9		\$468	\$477	\$491	\$510	\$531	\$553	\$581	\$609
DIMENSIONS: W 20 D 20 H 48.25 SW 20 SD 16 SH 30 CARTONED WEIGHT 42 CUBIC FEET 16												

**SPECIFICATIONS FOR COMMUNITY  
CARRIAGE COLLECTION**  
**MODELS: 401A – 401C – 403A – 403C – 408A – 408C**

**Wood Species:** Oak

**Details of Construction:** All chair parts are constructed from solid wood. All joints are connected together with solid wood, round tenons and assembly glue at each joint. The back is steam bent for maximum comfort and style. Front and back posts are lathe turned. The legs, as well as the spindles are wedged into the seat and secured with assembly glue.

**Finish:** Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

**Upholstery:** Each seat is upholstered with 1” high density polyurethane to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, Technical Bulletin #117.

<b>Dimensions:</b>	<b><u>401A, C</u></b>	<b><u>403A, C</u></b>	<b><u>408A, C</u></b>
	Width: 23”	Width: 20 ½”	Width: 20”
	Depth: 23”	Depth: 21 ½”	Depth: 20”
	Height: 38”	Height: 38”	Height: 48 ¼”
	Seat Width: 19”	Seat Width: 18”	Seat Width: 20”
	Seat Depth: 16”	Seat Depth: 16”	Seat Depth: 16”
	Seat Height: 18”	Seat Height: 18”	Seat Height: 30”
	Arm Height: 28”		