



MODEL 283A (SHOWN)



MODEL 288A (SHOWN)

AVAILABLE IN 13 METAL FINISHES.  
WOOD SEAT SPECIES: BEECH IN 13 FINISHES.  
SEE PAGE 221.

OPTIONAL LASER ENGRAVED BACK IMPRINT  
AVAILABLE. SEE PAGE 15 FOR PRICING  
AND ARTWORK SPECIFICATIONS.



WOOD




METAL



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD
ARMLESS MODEL (SPECIFY BACK OPTION)				
283A	WOOD SEAT			\$261
DIMENSIONS: W 16.5 D 16 H 30 SW 16.5 SD 16 SH 17.5 CARTONED WEIGHT 18 CUBIC FEET 9				
BARSTOOL MODEL (SPECIFY BACK OPTION)				
288A	WOOD SEAT			\$309
DIMENSIONS: W 16.5 D 16 H 42 SW 16.5 SD 16 SH 30 CARTONED WEIGHT 25 CUBIC FEET 13				



A BACK (WOOD)



B BACK (WOOD)




C BACK (WOOD)



D BACK (FABRIC)  
\$65 UPCHARGE



E BACK (METAL)  
SAME FINISH AS  
FRAME



F BACK (METAL)  
SAME FINISH AS  
FRAME



G BACK (METAL)  
SAME FINISH AS  
FRAME

# SPECIFICATIONS FOR COMMUNITY WALKER COLLECTION MODELS: 283A & 288A

**Details of Material:**    Seat: Contoured plywood; ¾”  
                                  Top: Exposed Grade, Beech plywood – ¾”  
                                  Back Posts: 18 gauge, metal square tube – 1 ¼”  
                                  Front Posts: 18 gauge, metal square tube – 1 ¼”  
                                  Seat Rim: 18 gauge, metal square tube – ¾”

**Details of Construction:**    Metal Frame Construction: Mig welds at all construction points.  
  Seat Assembly: Attached with 4 screws through metal tabs.  
  Back Assembly: Attached with 2 screws through metal tabs.

**Hardware:**                    Each chair is equipped standard with 1 ¼” clear K-resin rocker glides.

**Wood Finish:**                Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

**Metal Finish:**                Each frame is thoroughly cleaned of contaminants with a phosphorus bath and dried in an oven. A powder coat is applied to the frame and dried in an oven.

**Upholstery:**                 Each seat is upholstered with a piece of poly foam that measures 1 ½” thick. The seat is upholstered in a pneumatic press to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, Technical Bulletin #117.

<b>Dimensions:</b>	<u>283A</u>		<u>288A</u>	
	Width:	16 ½”	Width:	16 ½”
	Depth:	16”	Depth:	16”
	Height:	30”	Height:	42”
	Seat Width:	16 ½”	Seat Width:	16 ½”
	Seat Depth:	16”	Seat Depth:	16”
	Seat Height:	17 ½”	Seat Height:	30”