

DIMENSION
TWO POSITION



MODEL 21D (SHOWN)



MODEL 20B (SHOWN)

 ALL DIMENSION MODELS ON GSA CONTRACT.



WOOD SPECIES: OAK IN 14 FINISHES.
SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED
WITH FLEX-WEB FOR ADDED COMFORT
AND SUPPORT.

TWO POSITION RECLINING ACTION ALLOWS
MOVEMENT. ARM HEIGHT IS 25.25 WHEN IN
RECLINED POSITION.



OPTIONAL LASER ENGRAVED BACK IMPRINT
AVAILABLE. SEE PAGE 15 FOR PRICING
AND ARTWORK SPECIFICATIONS.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD	B/COM	C	D/COL	E	F	G	L	M
ARM MODELS												
21A	ALL WOOD			\$270								
21B	UPHOLSTERED BACK	.667	14.667		\$326	\$335	\$347	\$364	\$382	\$402	\$427	\$452
21C	UPHOLSTERED SEAT	.75	16.5		\$326	\$336	\$350	\$369	\$389	\$412	\$440	\$468
21D	UPHOLSTERED SEAT/BACK	.75	16.5		\$369	\$379	\$393	\$411	\$432	\$455	\$483	\$511

DIMENSIONS: W|21 D|24 H|31.25 SW|19 SD|18 SH|16 AH|23.625 CARTONED WEIGHT|32 CUBIC FEET|14



ARMLESS MODELS												
20A	ALL WOOD			\$256								
20B	UPHOLSTERED BACK	.667	14.667		\$288	\$296	\$309	\$325	\$344	\$364	\$389	\$414
20C	UPHOLSTERED SEAT	.75	16.5		\$306	\$315	\$330	\$348	\$369	\$391	\$420	\$448
20D	UPHOLSTERED SEAT/BACK	.75	16.5		\$343	\$352	\$366	\$385	\$405	\$428	\$456	\$484

DIMENSIONS: W|21 D|24 H|31.25 SW|19 SD|18 SH|16 CARTONED WEIGHT|30 CUBIC FEET|14



**SPECIFICATIONS FOR COMMUNITY
DIMENSION COLLECTION
MODELS: 20A,B,C,D – 21A,B,C,D**

Wood: Chairs are constructed from select American red oak. All lumber is thoroughly air seasoned before kiln drying to a moisture content of 6% or less. The lumber is then allowed to temper before milling. Parts that are selected for steam bending are partially air seasoned before bending, then kiln dried to a moisture content of less than 6% after bending.

Details of Construction: The seat is made solid wood and is glued together with a high grade of glue and double saddled for maximum comfort and style. The back consists of a solid wood panel which is steam bent for maximum comfort and style. The seats and back are easily removed. All joints are connected together with mortise and tennon and glue. All rails, arms, front posts, back posts, stretchers, and rocker sled runners are made from 1 ¼” lumber. For additional strength, the rails are secured by a corner block, glue, and screws at each joint. The solid wood back is screwed to the chair frame through the back posts.

Finish: Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

Hardware: Each chair is equipped standard with rubber cushion nickel plated glides.

Upholstery: The upholstered back consists of a 1” polyurethane pad. The upholstered seat consists of Ultra-Flex rubber sheeting and a 1 ½” high density polyurethane pad. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, and Technical Bulletin #117.

Dimensions:	<u>20A,B,C,D</u>	<u>21A,B,C,D</u>
	Width: 21”	Width: 21”
	Depth: 24”	Depth: 24”
	Height: 31 ¼”	Height: 31 ¼”
	Seat Width: 19”	Seat Width: 19”
	Seat Depth: 18”	Seat Depth: 18”
	Seat Height: 16”	Seat Height: 16”
		Arm Height: 23 ⅝”