



MODEL 6923C (SHOWN)



MODEL 6928C (SHOWN)

WOOD SPECIES: BEECH IN 13 FINISHES. SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED WITH FLEX-WEB FOR ADDED COMFORT AND SUPPORT.

OPTIONAL LASER ENGRAVED BACK IMPRINT AVAILABLE. SEE PAGE 15 FOR PRICING AND ARTWORK SPECIFICATIONS.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING		D/COL	E	F	G	L	M	
				WOOD	B/COM C							
ARMLESS MODEL												
6923C	UPHOLSTERED SEAT	.75	9		\$320	\$329	\$343	\$362	\$383	\$405	\$433	\$462
DIMENSIONS: W   19.5 D   19.5 H   33.75		SW   19.5 SD   17.5 SH   18		CARTONED WEIGHT   20 CUBIC FEET   9								
BARSTOOL MODEL												
6928C	UPHOLSTERED SEAT	.75	9		\$363	\$372	\$386	\$405	\$426	\$448	\$476	\$504
DIMENSIONS: W   17.75 D   18.75 H   45.5		SW   17.75 SD   16.25 SH   30		CARTONED WEIGHT   28 CUBIC FEET   13								

**SPECIFICATIONS FOR COMMUNITY  
ELLIPSE COLLECTION  
MODELS: 6923C – 6928C**

**Wood Species:** Beech

**Details of Construction:** All chair parts are constructed from solid wood. All joints are connected together using mortise and tennon construction and assembly glue at each joint. All frames are reinforced with corner blocks which are properly fitted into the four corners of the seat frame and securely screwed and glued to the rails. For additional strength and stability, a steel screw is placed through each corner block and into the center of the each adjoining leg.

**Finish:** Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

**Hardware:** Each chair is equipped standard with rubber cushion nickel plated glides.

**Upholstery:** Each seat is upholstered with 1-1/2" high density polyurethane to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, Technical Bulletin #117.

**Dimensions:** 6923C

Width: 19 1/2"

Depth: 19 1/2"

Height: 33 3/4"

Seat Width: 19 1/2"

Seat Depth: 17 1/2"

Seat Height: 18"

6928C

Width: 17 3/4"

Depth: 18 3/4"

Height: 45 1/2"

Seat Width: 17 3/4"

Seat Depth: 16 1/4"

Seat Height: 30"