

KINSEY



MODEL 1381D (SHOWN)



MODEL 1383D (SHOWN)



WOOD SPECIES: BEECH IN 13 FINISHES.
SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED
WITH FLEX-WEB FOR ADDED COMFORT
AND SUPPORT.

| MODEL | DESCRIPTION | COM YRD. | COL SQ. FT. | PRICING | | | D/COL | E | F | G | L | M |
|-----------------------------------|-----------------------|-------------|----------------|---------|--------------------|--------------------|--------------|---------------|-------|-------|-------|---|
| | | | | B/COM | C | | | | | | | |
| ARM MODEL | | | | | | | | | | | | |
| 1381D | UPHOLSTERED SEAT/BACK | 1.75 | 38.5 | \$543 | \$565 | \$598 | \$641 | \$690 | \$742 | \$808 | \$873 | |
| DIMENSIONS: W 23.75 D 23.375 H 38 | | SW 20 | SD 19.625 | SH 18.5 | AH 25.25 | CARTONED WEIGHT 26 | | CUBIC FEET 12 | | | | |
| ARMLESS MODEL | | | | | | | | | | | | |
| 1383D | UPHOLSTERED SEAT/BACK | 1.75 | 38.5 | \$484 | \$506 | \$539 | \$582 | \$631 | \$683 | \$749 | \$814 | |
| DIMENSIONS: W 20 D 23.375 H 38 | | SW 20 | SD 19.625 | SH 20 | CARTONED WEIGHT 22 | | CUBIC FEET 9 | | | | | |

**SPECIFICATIONS FOR COMMUNITY
KINSEY COLLECTION
MODELS: 1381D & 1383D**

Wood Species: Beech

Details of Construction: All chair parts are constructed from solid wood. All joints are connected together using mortise and tennon construction and assembly glue at each joint. All frames are reinforced with corner blocks which are properly fitted into the four corners of the seat frame and securely screwed and glued to the rails. For additional strength and stability, a steel screw is placed through each corner block and into the center of the each adjoining leg.

Finish: Back posts, tops, seat rims and stretchers are steam bent for maximum strength. Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

Upholstery: Each seat is upholstered with 1 ½” high density polyurethane to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, Technical Bulletin #117.

Hardware: Each chair is equipped standard with rubber cushion nickel plated glides.

| Dimensions: | <u>1381D</u> | <u>1383D</u> |
|--------------------|---------------------|---------------------|
| | Width: 23 ¾” | Width: 20” |
| | Depth: 23 ¾” | Depth: 23 ¾” |
| | Height: 38” | Height: 38” |
| | Seat Width: 20” | Seat Width: 20” |
| | Seat Depth: 19 ⅝” | Seat Depth: 19 ⅝” |
| | Seat Height: 18 ½ ” | Seat Height: 20” |
| | Arm Height: 25 ¼ ” | |