



MODEL MA1561F (SHOWN)



MODEL MA1561J (SHOWN)

WOOD SPECIES: MAPLE IN 13 FINISHES. SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED WITH FLEX-WEB FOR ADDED COMFORT AND SUPPORT.

OPTIONAL BLACK ANTIQUE TRIM NAILS AVAILABLE. SPECIFY AS AN OPTION WHEN ORDERING. NO UPCHARGE.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING B/COM	C	D/COL	E	F	G	L	M
ARM MODEL											
MA 1561F	UPHOLSTERED	2	44	\$476	\$501	\$538	\$588	\$643	\$703	\$778	\$853
MA 1563F	UPHOLSTERED W/CASTERS	2	44	\$554	\$579	\$617	\$667	\$722	\$782	\$857	\$932
DIMENSIONS: W 24.5 D 26 H 30 SW 20 SD 20 SH 19.5 AH 25		CARTONED WEIGHT 34		CUBIC FEET 14							
ARM MODEL WITH TRIM NAILS											
MA 1561J	UPHOLSTERED	2	44	\$517	\$542	\$579	\$629	\$684	\$744	\$819	\$894
MA 1563J	UPHOLSTERED W/CASTERS	2	44	\$596	\$621	\$658	\$708	\$763	\$823	\$898	\$973
DIMENSIONS: W 24.5 D 26 H 30 SW 20 SD 20 SH 19.5 AH 25		CARTONED WEIGHT 34		CUBIC FEET 14							

**SPECIFICATIONS FOR COMMUNITY
MADISON COLLECTION**
MODELS: MA1561F – MA1561J – MA1563F – MA1563J

Wood Species: Maple

Details of Construction: All chair parts are constructed from solid wood. All joints are connected together with spiraled dowels and assembly glue at each joint. All frames are reinforced with corner blocks which are properly fitted into the four corners of the seat frame and securely screwed and glued to the rails. For additional strength and stability, a steel screw is placed through each corner block and into the center of each adjoining leg.

Finish: Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

Hardware: Each chair is equipped standard with nickel plated tap in glides.

Upholstery: Each seat is upholstered with 3 ¼” high density polyurethane to assure consistency in thickness and comfort. The back and arms are upholstered with high density polyurethane for durability and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, Technical Bulletin #117.

Dimensions:

MA1561F – MA1561J – MA1563F – MA1563J

Width: 24 ½”
Depth: 26”
Height: 30”
Seat Width: 20”
Seat Depth: 20”
Seat Height: 19 ½”
Arm Height: 25”