



MODEL 233C (SHOWN)



MODEL 238A (SHOWN)



MODEL 239C (SHOWN)

AVAILABLE IN 13 METAL FINISHES.
WOOD SEAT SPECIES: BEECH IN 13 FINISHES.
SEE PAGE 221.

UPHOLSTERED SEATS CONSTRUCTED
WITH FLEX-WEB FOR ADDED COMFORT
AND SUPPORT.

SWIVEL STOOLS HAVE 360° SWIVEL CAPABILITY.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING WOOD	B/COM	C	D/COL	E	F	G	L	M
ARMLESS MODEL												
233A	WOOD SEAT			\$236								
233C	UPHOLSTERED SEAT	.75	9		\$233	\$242	\$256	\$275	\$296	\$318	\$346	\$375
DIMENSIONS: W 18 D 19 H 32.5 SW 17 SD 17 SH 18 CARTONED WEIGHT 21 CUBIC FEET 9												
BARSTOOL MODEL												
238A	WOOD SEAT			\$282								
238C	UPHOLSTERED SEAT	.75	9		\$279	\$288	\$302	\$321	\$342	\$364	\$392	\$421
DIMENSIONS: W 19 D 20 H 43.25 SW 17 SD 17 SH 30 CARTONED WEIGHT 28 CUBIC FEET 13												
SWIVEL BARSTOOL MODEL												
239A	WOOD SEAT			\$331								
239C	UPHOLSTERED SEAT	.75	9		\$328	\$337	\$351	\$370	\$391	\$413	\$441	\$470
DIMENSIONS: W 20 D 20 H 44 SW 17 SD 16 SH 30 CARTONED WEIGHT 31 CUBIC FEET 13												

**SPECIFICATIONS FOR COMMUNITY
NELSON COLLECTION
MODELS: 233A, C – 238A,C – 239A, C**

Wood Species: Beech

Details of Construction: Seat: Solid wood seat; 1” thick
Upholstered Grade Seat: Uph. grade plywood webbed with sheet wedding – $\frac{5}{8}$ ”

All chair parts are constructed from 18 gauge metal. All joints are connected together with a mig weld. The seats are attached with screws through 4 tabs welded to the frame.

Wood Finish: Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

Metal Finish: Each frame is thoroughly cleansed of contaminates with a phosphorus bath and dried in an oven. A powder coat is applied to the frame and dried in an oven.

Upholstery: Each seat is upholstered with 2” high density polyurethane in a pneumatic press to assure consistency in thickness and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, and Technical Bulletin #117.

Dimensions:	<u>233A, C</u>	<u>238A, C</u>	<u>239A, C</u>
	Width: 18”	Width: 19”	Width: 20”
	Depth: 19”	Depth: 20”	Depth: 20”
	Height: 32 ½”	Height: 43 ¼”	Height: 44”
	Seat Width: 17”	Seat Width: 17”	Seat Width: 17”
	Seat Depth: 17”	Seat Depth: 17”	Seat Depth: 16”
	Seat Height: 18”	Seat Height: 30”	Seat Height: 30”