

STERLING



MODEL ST1171D (SHOWN)



MODEL ST1173D (SHOWN)



STACKS UP TO TEN HIGH (SHOWN ON DOLLY)



DOLLY ST1100

WOOD SPECIES: BEECH IN 13 FINISHES. SEE PAGE 221.

OPTIONAL GANGING BRACKET AVAILABLE. SPECIFY AS AN OPTION WHEN ORDERING. ADD \$20 LIST PER GANGING DEVICE.



OPTIONAL CASTERS AVAILABLE ON ALL LEGS. ADD \$75 LIST FOR SET OF 4 CASTERS.



MODEL	DESCRIPTION	COM YRD.	COL SQ. FT.	PRICING		D/COL	E	F	G	L	M
				B/COM	C						
ARM MODEL											
ST1171D	UPHOLSTERED SEAT/BACK	1	22	\$289	\$301	\$320	\$345	\$373	\$403	\$440	\$478
DIMENSIONS: W 20.5 D 23 H 33 SW 17.25 SD 17.5 SH 18 AH 25		CARTONED WEIGHT 25		CUBIC FEET 12							
ARMLESS MODEL											
ST1173D	UPHOLSTERED SEAT/BACK	1	22	\$289	\$301	\$320	\$345	\$373	\$403	\$440	\$478
DIMENSIONS: W 20.5 D 23 H 33 SW 17.25 SD 17.5 SH 18		CARTONED WEIGHT 25		CUBIC FEET 12							
DOLLY											
ST1100	LOCKING CASTERS			\$257							
DIMENSIONS: W 16 D 24 H 24		CARTONED WEIGHT 12		CUBIC FEET 7							

**SPECIFICATIONS FOR COMMUNITY  
STERLING COLLECTION  
MODELS: ST1171D – ST1173D**

**Wood Species:** Beech

**Details of Construction:** All chair parts are constructed from solid plywood with beech veneer. The frame is assembled with barrel nut assembly and glue at each joint. The seat is attached with 4 screws from the bottom side and the back is attached with 4 exterior fasteners.

**Finish:** Each chair has an even coat of a no-wipe stain, followed by a coat of sealer. A light sanding is given and then oven dried for 30 minutes. Another coat of catalyzed sealer is applied and oven dried for another 30 minutes. Another light sanding process is performed to assure a smooth finish. Then the product is sprayed with a 45 sheen catalyzed lacquer and oven dried for an additional 30 minutes. Then there is a 30 minute cool down period before final inspection.

**Hardware:** Each chair is equipped standard with nickel plated tap in glides.

**Upholstery:** Each seat is upholstered with 1 ½” high density polyurethane to assure consistency in thickness and comfort. The backs are upholstered with 1” high density polyurethane for durability and comfort. All upholstery materials pass the California Fire Retardant Code, Class 1, Commercial Standard 191-53, Technical Bulletin #117.

**Dimensions:** **ST1171D**

Width: 20 ½”  
Depth: 23”  
Height: 33”  
Seat Width: 17 ¼”  
Seat Depth: 17 ½”  
Seat Height: 18”  
Arm Height: 25”

**ST1173D**

Width: 20 ½”  
Depth: 23”  
Height: 33”  
Seat Width: 17 ¼”  
Seat Depth: 17 ½”  
Seat Height: 18”